

H3530 -

□□: H3530

□□□□□□□□□□□□2□□□□□□

[illegible]

□□□□

湿度精度	0 to 100%
湿度解析度	±2.5%(5 to 95% at 23°C)
温度精度	±0.4°C
温度	0.1°C, 0.1%RH
湿度精度	2s
湿度解析度	0.1%RH
温度	±0.1°C, ±0.1%RH
A/D converter	±1.5°C, ±0.1%RH, T<25°C, RH>30% -60 to +80°C
湿度精度	±0.1°C, ±0.1%RH
温度	-30 to +80°C
IP rating	IP40
湿度精度	2
湿度解析度	50V, 2A, 60VA
湿度精度	3
湿度精度	±0.1°C, ±0.1%RH
湿度	±0.1°C, ±0.1%RH
LAN	RJ-45, 10Base-T, 100Base-TX
湿度	WWW, ModbusTCP, SNMPv1, SOAP
湿度	E-mail (SMTP), SNMP Trap, Syslog
湿度	T-Sensor, Telnet, keyboard
LCD	±0.1°C, ±0.1%RH, LCD
湿度	9-30Vdc, 1W
湿度	co-axial, 5.5 x 2.1mm
湿度	136 x 191 x 45mm (W x H x D), 53mm
湿度	340g
湿度	3