

H3531P - - kopie - kopie

: H3531P-4



T+RH 25 bar
H3531P 3 2

	0 to 100%
	$\pm 2.5\%$ 5 to 95% at 23°C
	$\pm 0.4^{\circ}\text{C}$
	0.1°C, 0.1%RH
	2s
	-60 to +80°C
	1.5°C +10°C +25°C
	2.0°C +0°C +25°C
	3.0°C -10°C +25°C
	6.0°C -20°C +25°C
	$\pm 1.5\text{g/m}^3$ T < 25°C 0 to 400 g/m3
	$\pm 2\text{g/kg}$ T < 35°C 0 to 550 g/kg
	$\pm 2\text{g/kg}$ T < 35°C 0 to 995 g/kg
	$\pm 3\text{kJ/kg}$ T < 25°C : 0 to 995 kJ/kg
Temperature compensation of the humidity sensor	all temperature range
	-30 to +80°C
IP	IP40
	2
	50V, 2A, 60VA
	3
	500ms
	0 to +0.5V
	+3.0 to +30V
	-

LAN	RJ-4510Base-T100Base-TX
	WWW, ModbusTCP, SNMPv1, SOAP
	E-mail (SMTP)SNMP TrapSyslog
	T-Sensor, Telnet, keyboard
LCD	+70°C+70°CLCD
	0.025mm -
	9 to 30Vdc, 1W
	co-axial, 5.5 x 2.1mm
	G1/2O
	1m, 2m or 4m
	136 x 159 x 45 mm (W x H x D), 150mm18mm
	460g - 1
	3