

H7531 -



: H7531

2
 H753132
 3

3
 2

3

	0 to 100%
	±2.5%5 to 95% at 23°C
	±0.4°C
	600 to 1100hPa
	±1.3hPa at 23°C
	0.1°C, 0.1%RH, 0.1hPa
	2s
	hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2
	±1.5°C<25°C > RH>30% -60 to +80 °C
	±1.5g/m3 T < 25°C 0 to 400 g/m3
	±2g/kg T < 35°C 0 to 550 g/kg
	±2g/kg T < 35°C 0 to 995 g/kg
	±3kJ/kg T < 25°C : 0 to 995 kJ/kg
	-30 to +80°C
IP	IP40
	2
	50V, 2A, 60VA
	3
	500 ms
	0 to +0.5 V
	+3.0 to +30V
	-
LAN	RJ-4510Base-T100Base-TX

Protocol	WWW, ModbusTCP, SNMPv1, SOAP
Alerts	E-mail (SMTP), SNMP Trap, Syslog
Temperature	T-Sensor, Telnet, RS485
LCD display	Operating temperature: +70°C, Storage temperature: -70°C, LCD display
Thickness	0.025mm - 0.05mm
Power	9-30Vdc, max 1W
Dimensions	Standard, 5.5 x 2.1mm
Length	1m, 2m or 4m
Weight	136 x 159 x 45mm (W x H x D), max 88mm, max 18mm
Material	max 410g - max 1m
Quantity	3