

Temperature probe for COMETEO Solar Shields F8x00, Pt1000TR160/C, with CINCH connector, cable 25 cm

□□: SN250VC



Precise IP67 watertight probe -30 to +80°C for use in COMETEO solar radiation shields F8800 and F8900.

Transducer itself is then located inside of the top cover of the COMETEO solar shield.

Tolerance $t = \pm(0.30 + 0.005 \cdot |t|)$ - class B in accordance with IEC751. Polyamide enclosure with shielded PVC cable of 25cm length. Enclosure diameter 6mm, length 20mm. With CINCH connector.

□□□□

TEMPERATURE SENSOR	
Measuring range	-30 to +80 °C
Accuracy	$\pm (0.3 + 0.005 \cdot t)$ at °C
Accuracy class	A
Time response	$t_{0.5} < 12 \text{ s}$ (in flowing water at $> 0.2 \text{ m/s}$) $t_{50} < 12 \text{ s}$, $t_{90} < 32 \text{ s}$ (in liquid)
Type of sensing element	Pt1000
Temperature coefficient	3850 ppm / °C
GENERAL TECHNICAL DATA	
Wire connection	2-wire connection
Material of the case	POLYAMIDE-based plastic
Dimensions of the case	length 20 mm; diameter $5.7 \pm 0.1 \text{ mm}$
Lead-in cable	PVC shielded
Length of lead-in cable	25 cm
Connector	CINCH
IP protection	IP67
Warranty	30 months