

**T0211P - kopie**

□□: T0211P-2

25bar 1 2 4

NEW - AC Power - 24 Vac !



1111

|         |                                                          |
|---------|----------------------------------------------------------|
| 顯示範圍    | 0 to 100%                                                |
| 顯示準確度   | ±2.5% 0 to 95% at 23°C                                   |
| 溫度範圍    | ±0.4°C -30 to +100°C<br>±0.4% from reading over +100°C   |
| 溫度準確度   | ±0.4°C                                                   |
| 溫度範圍    | -60 to +80°C                                             |
| 溫度準確度   | 1.5°C 0 to +10°C<br>±2.5°C +25°C                         |
| 溫度準確度   | 2.0°C 0 to +10°C<br>±2.5°C +25°C                         |
| 溫度準確度   | 3.0°C 0 to +10°C<br>±2.5°C +25°C                         |
| 溫度準確度   | 6.0°C 0 to +10°C<br>±2.5°C +25°C                         |
| 溫度準確度   | ±1.5g/m³ 0 to 25°C<br>0 to 400 g/m³                      |
| 溫度準確度   | ±2g/kg 0 to 35°C<br>0 to 550 g/kg                        |
| 溫度準確度   | ±2g/kg 0 to 35°C<br>0 to 995 g/kg                        |
| 溫度準確度   | ±3kJ/kg 0 to 25°C<br>0 to 995 kJ/kg                      |
| 溫度準確度   | -30 to +80°C                                             |
| LCD顯示範圍 | 0 to +70°C<br>0 to +70°C LCD顯示                           |
| 顯示範圍    | 0 to 10V, 0 to 100V                                      |
| 顯示範圍    | 0 to 10V, 0 to 100V                                      |
| 顯示範圍    | 0.025mm - 0.1mm                                          |
| IP等級    | IP65 0 to 100V, IP40 0 to 100V                           |
| 顯示範圍    | 15-30Vdc, 0 to 20mA, 24Vac                               |
| 顯示範圍    | G1/2" O.D.                                               |
| 顯示範圍    | 1m, 2m or 4m                                             |
| 顯示範圍    | 88.5 x 114 x 39.5 mm (W x H x D), 0 to 150 mm, 0 to 18mm |
| 顯示範圍    | 0 to 260g                                                |
| 顯示範圍    | 3"                                                       |