

T0211P - kopie - kopie

□□: T0211P-4

25bar 1 2 4

NEW - AC Power - 24 Vac !



□□□□

顯示範圍	0 to 100%
顯示準確度	±2.5% 0 to 95% at 23°C
溫度範圍	±0.4°C -30 to +100°C ±0.4% from reading over +100°C
溫度準確度	±0.4°C
溫度範圍	-60 to +80°C
溫度準確度	1.5°C 0 to +10°C ±2.5°C +25°C
溫度準確度	2.0°C 0 to +10°C ±2.5°C +25°C
溫度準確度	3.0°C 0 to +10°C ±2.5°C +25°C
溫度準確度	6.0°C 0 to +10°C ±2.5°C +25°C
溫度準確度	±1.5g/m³ 0 to 25°C 0 to 400 g/m³
溫度準確度	±2g/kg 0 to 35°C 0 to 550 g/kg
溫度準確度	±2g/kg 0 to 35°C 0 to 995 g/kg
溫度準確度	±3kJ/kg 0 to 25°C 0 to 995 kJ/kg
溫度準確度	-30 to +80°C
LCD顯示範圍	0 to +70°C 0 to +70°C LCD顯示
顯示範圍	0 to 10V, 0 to 10V
顯示範圍	0 to 10V, 0 to 10V
顯示範圍	0.025mm - 0.025mm
IP等級	IP65 0 to 10V, IP40 0 to 10V
顯示範圍	15-30Vdc, 0 to 20mA, 24Vac
顯示範圍	G1/2" O.D.
顯示範圍	1m, 2m or 4m
顯示範圍	88.5 x 114 x 39.5 mm (W x H x D), 0 to 150 mm, 0 to 18mm
顯示範圍	0 to 260g
顯示範圍	3"