

T0213 0-10V

Model: T0213



0-10V output

150mm probe

NEW - AC Power - 24 Vac !

Table

Humidity	0 to 100%
Humidity accuracy	$\pm 2.5\%$ RH 5 to 95% at 23°C
Temperature	$\pm 0.4^{\circ}\text{C}$ -30 to +100°C $\pm 0.4\%$ from reading over +100°C
Dew point	Dew point
Accuracy and range of dew point temperature output - for more details see graphs	$\pm 1.5^{\circ}\text{C}$ at ambient temperature $T < 25^{\circ}\text{C}$ and $\text{RH} > 30\%$ range -60 to +80 °C
Mass concentration	$\pm 1.5\text{g/m}^3$ $T < 25^{\circ}\text{C}$ 0 to 400 g/m ³
Mass concentration	$\pm 2\text{g/kg}$ $T < 35^{\circ}\text{C}$ 0 to 550 g/kg
Mass concentration	$\pm 2\text{g/kg}$ $T < 35^{\circ}\text{C}$ 0 to 995 g/kg
Mass concentration	$\pm 3\text{kJ/kg}$ $T < 25^{\circ}\text{C}$ 0 to 995 kJ/kg
Temperature range	-30 to +80°C
LCD display	Display +70°C, LCD display
Output	Output
Output	0-10V, 0-10V
Output	Output
Output	0.025mm - 0.025mm
IP rating	IP65, IP40
Power	15-30Vdc, 20mA, 24Vac
Dimensions	88.5 x 250 x 39.5 mm (W x H x D), 150 mm
Weight	225g
Warranty	3