

T0213D

Model: T0213D

Temperature, Humidity, Dew Point, Weight, Moisture

Measurement range: 150mm

NEW - AC Power - 24 Vac !



Model

Temperature	0 to 100%
Humidity	$\pm 2.5\%$ RH 5 to 95% at 23°C
Dew Point	$\pm 0.4^{\circ}\text{C}$ -30 to $+100^{\circ}\text{C}$ $\pm 0.4\%$ from reading over $+100^{\circ}\text{C}$
Weight	0.025mm - 0.05mm
Moisture	$\pm 1.5^{\circ}\text{C}$ RH > 30% RH -60 to $+80^{\circ}\text{C}$
Moisture	$\pm 1.5\text{g/m}^3$ T < 25°C RH 0 to 400 g/m3
Moisture	$\pm 2\text{g/kg}$ T < 35°C RH 0 to 550 g/kg
Moisture	$\pm 2\text{g/kg}$ T < 35°C RH 0 to 995 g/kg
Moisture	$\pm 3\text{kJ/kg}$ T < 25°C RH: 0 to 995 kJ/kg
Moisture	-30 to $+80^{\circ}\text{C}$
LCD	0.025mm - 0.05mm LCD
Moisture	0.025mm - 0.05mm
Moisture	0-10V, 0.025mm - 0.05mm
Moisture	0.025mm - 0.05mm
Moisture	0.025mm - 0.05mm
IP	IP65, IP40
Moisture	15-30Vdc, 20mA, 24Vac
Moisture	88.5 x 250 x 39.5 mm (W x H x D), 150 mm
Moisture	225g
Moisture	3