

T3110Ex



Model: T3110Ex

ATEX certification information and details.

ATEX group.

Table

Humidity	0 to 100%
Humidity accuracy	±2.5% RH 5 to 95% at 23°C
Temperature	±0.4°C
Temperature range	Full range
Temperature accuracy	±1.5°C (T < 25°C) / ±0.5°C (T > 25°C) / ±0.5°C (RH > 30%) / ±0.5°C (-60 to +80°C)
Temperature range	±1.5g/m³ (T < 25°C) / ±0.5g/m³ (T > 25°C) / ±0.5g/m³ (0 to 400 g/m³)
Temperature range	±2g/kg (T < 35°C) / ±0.5g/kg (T > 35°C) / ±0.5g/kg (0 to 550 g/kg)
Temperature range	±2g/kg (T < 35°C) / ±0.5g/kg (T > 35°C) / ±0.5g/kg (0 to 995 g/kg)
Temperature range	±3kJ/kg (T < 25°C) / ±0.5kJ/kg (T > 25°C) / ±0.5kJ/kg (0 to 995 kJ/kg)
Temperature range	-30 to +60°C
Temperature range	±0.5°C
LCD display	Backlight +70°C / Backlight +70°C / LCD display
Temperature range	Full range
Output - 4-20mA	4-20mA, 2-wire
Temperature range	Full range PC
Temperature range	0.025mm - 0.05mm
IP rating	IP65 / IP40
Power	9-30Vdc
Size	88.5 x 170 x 39.5 mm (W x H x D), 75 mm
Weight	150g
Life	3 years