

T3111P - □□□□□□□□□□□□□□□□4-20mA□□□□

□□: T3111P

T+RH
bar 1m,2m,4m /

[illegible]

1111

測試範圍	0 to 100%
測試準確度	±2.5% 0 to 95% at 23°C
測試溫度	±0.4°C -30 to +100°C ±0.4% 0 to +100°C
測試時間	測試時間
測試溫度	-60 to +80°C
測試溫度	1.5°C 0 to +10°C 0 to +25°C
測試溫度	2.0°C 0 to +0°C 0 to +25°C
測試溫度	3.0°C 0 to -10°C 0 to +25°C
測試溫度	6.0°C 0 to -20°C 0 to +25°C
測試溫度	±1.5g/m3 0 to 25°C 0 to 400 g/m3
測試溫度	±2g/kg 0 to 35°C 0 to 550 g/kg
測試溫度	±2g/kg 0 to 35°C 0 to 995 g/kg
測試溫度	±3kJ/kg 0 to 25°C 0 to 995 kJ/kg
測試溫度	-30 to +80°C
LCD顯示範圍	0 to +70°C 0 to +70°C LCD顯示
測試溫度	測試溫度
測試-2000	4-20mA 0 to 20mA
測試溫度	測試溫度
測試溫度	0.025mm - 0.05mm
IP等級	IP65, IP40
測試	9 to 30Vdc
測試	co-axial, 5.5 x 2.1mm
測試溫度	G1/2" O.D.
測試溫度	1m, 2m or 4m
測試	88.5 x 114 x 39.5mm (W x H x D), 150mm 18mm
測試	260g - 1000g

