

T3111P - 4-20mA - kopie - kopie

Model: T3111P-4

Temperature and Humidity (T+RH) sensor with 25 bar pressure sensor. 1m, 2m, 4m cable lengths. 1 year warranty.



Table

Temperature range	0 to 100%
Accuracy	±2.5% RH at 23°C
Resolution	±0.4°C / -30 to +100°C ±0.4% RH at +100°C
Operating temperature	Operating temperature
Storage temperature	-60 to +80°C
Temperature stability	1.5°C / +10°C to +25°C
Temperature stability	2.0°C / +0°C to +25°C
Temperature stability	3.0°C / -10°C to +25°C
Temperature stability	6.0°C / -20°C to +25°C
Humidity range	±1.5g/m³ T < 25°C 0 to 400 g/m³
Humidity range	±2g/kg T < 35°C 0 to 550 g/kg
Humidity range	±2g/kg T < 35°C 0 to 995 g/kg
Humidity range	±3kJ/kg T < 25°C 0 to 995 kJ/kg
Operating temperature	-30 to +80°C
LCD display	Operating temperature +70°C LCD display
Operating temperature	Operating temperature
Output - 20mA	4-20mA
Operating temperature	Operating temperature
Operating temperature	0.025mm - Operating temperature
IP rating	IP65, IP40
Power	9 to 30Vdc
Dimensions	co-axial, 5.5 x 2.1mm
Operating temperature	G1/2" O-ring
Operating temperature	1m, 2m or 4m
Weight	88.5 x 114 x 39.5mm (W x H x D), 150mm 18mm
Weight	260g - 1kg

