

T3419 - kopie - kopie

□□: T3419-4

[illegible]

1m



1111

顯示器尺寸	0 to 100%
顯示器亮度	±2.5% 1000cd/m2 5 to 95% at 23°C
顯示器溫度	±0.4°C -30~+100°C ±0.4% 1000cd/m2 +100°C
顯示器濕度	100%RH
顯示器壽命	-60 to +80 °C
顯示器電壓	±1.5°C 1000cd/m2 T<25°C RH>30% -60 to +80 °C
顯示器電流	±1.5g/m3 1000cd/m2 T < 25°C 0 to 400 g/m3
顯示器電阻	±2g/kg 1000cd/m2 T < 35°C 0 to 550 g/kg
顯示器電容	±2g/kg 1000cd/m2 T < 35°C 0 to 995 g/kg
顯示器電感	±3kJ/kg 1000cd/m2 T < 25°C 0 to 995 kJ/kg
顯示器電阻	-30 to +80°C
LCD顯示器尺寸	1000cd/m2 +70°C 1000cd/m2 +70°C 1000cd/m2 LCD 1000cd/m2
顯示器電阻	1000cd/m2 1000cd/m2
顯示器電容	ModBus RTU, Advantech ADAM 1000cd/m2
顯示器電感	110 to 115200 Bd
顯示器電阻	0.025mm - 1000cd/m2
IP顯示器	IP65 1000cd/m2 IP40 1000cd/m2
顯示器電阻	9-30Vdc, 1000cd/m2 0.5W
顯示器電容	1m, 2m, 4m 1000cd/m2
顯示器電感	88.5 x 114 x 39.5 mm (W x H x D), 1000cd/m2 88 mm, 1000cd/m2 18mm
顯示器電阻	1000cd/m2 210g - 1m 1000cd/m2
顯示器電容	3000cd/m2