

T3419P - kopie - kopie

T3419P-4



OMET T3419P-4 is a digital pressure and temperature transmitter. It features a stainless steel housing and a black cable. The device is designed for use in industrial environments and can measure pressure up to 25 bar and temperature up to 100°C. It has a 4-wire connection and a 1m cable length.

OMET

Pressure range	0 to 100%
Accuracy	±2.5% (0 to 95% at 23°C)
Temperature range	±0.4°C (-30 to +100°C) / ±0.4% (0 to +100°C)
Temperature range	Temperature range
Temperature range	-60 to +80 °C
Temperature range	1.5°C (0 to +10°C) / +25°C
Temperature range	2.0°C (0 to +0°C) / +25°C
Temperature range	3.0°C (0 to -10°C) / +25°C
Temperature range	6.0°C (0 to -20°C) / +25°C
Temperature range	±1.5g/m3 (T < 25°C) / 0 to 400 g/m3
Temperature range	±2g/kg (T < 35°C) / 0 to 550 g/kg
Temperature range	±2g/kg (T < 35°C) / 0 to 995 g/kg
Temperature range	±3kJ/kg (T < 25°C) / 0 to 995 kJ/kg
Temperature range	-30 to +80°C
LCD display	Temperature +70°C / +70°C LCD display
Temperature range	Temperature range
ModBus RTU	ModBus RTU Advantech ADAM
ModBus RTU	110 to 115200 Bd
ModBus RTU	0.025mm - 0.025mm
IP rating	IP65 / IP40
Power supply	9-30Vdc, 0.5W
Power supply	G1/2" O-ring
Power supply	1m, 2m, 4m
Power supply	88.5 x 114 x 39.5 mm (W x H x D), 150mm, 18mm
Power supply	260g - 1m
Power supply	3