

T7311 - RS232 - kopie

Model: T7311-2

This is a copy of the original document.
 The original document is available in PDF format on the OMET website.



Features

Humidity	0 to 100%
Humidity Accuracy	±2.5% RH 5 to 95% at 23°C
Humidity Resolution	±0.4°C
Temperature	±0.1°C
Temperature Accuracy	±1.5°C (T < 25°C) RH > 30% -60 to +80 °C
Temperature Resolution	±1.5g/m³ (T < 25°C) 0 to 400 g/m³
Pressure Accuracy	±2g/kg (T < 35°C) 0 to 550 g/kg
Pressure Resolution	±2g/kg (T < 35°C) 0 to 995 g/kg
Pressure Accuracy	±3kJ/kg (T < 25°C) 0 to 995 kJ/kg
Pressure Resolution	600 to 1100hPa
Pressure Accuracy	±(1,3hPa+0.06% of reading) at 23°C from 800 to 1100hPa
Pressure Resolution	hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2
Pressure Accuracy	-30 to +80°C
LCD Display	Backlight +70°C, 70°C, LCD
Communication	ModBus
Protocol	ModBus RTU, Advantech ADAM
Speed	110 to 115200 Bd
Dimensions	0.025mm - 0.025mm
IP Rating	IP54, IP40
Power	9-30Vdc, 6mA
Wiring	1m, 2m or 4m
Weight	88.5 x 114 x 39.5 mm (W x H x D), 88 mm, 18mm
Material	290g - 1m
Life	3