

T7311 - RS232 - kopie - kopie

Model: T7311-4

A high-precision digital temperature and humidity sensor with an RS232 interface and an LCD display.



Features:

Temperature range	0 to 100%
Humidity range	±2.5% RH 5 to 95% at 23°C
Temperature accuracy	±0.4°C
Humidity accuracy	±0.4% RH
Operating temperature	±1.5°C (T < 25°C) RH > 30% -60 to +80 °C
Operating humidity	±1.5g/m³ (T < 25°C) 0 to 400 g/m³
Operating pressure	±2g/kg (T < 35°C) 0 to 550 g/kg
Operating energy	±2g/kg (T < 35°C) 0 to 995 g/kg
Operating power	±3kJ/kg (T < 25°C) 0 to 995 kJ/kg
Operating pressure	600 to 1100hPa
Operating pressure	±(1,3hPa+0.06% of full scale) at 23°C from 800 to 1100hPa
Operating pressure	hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2
Operating pressure	-30 to +80°C
LCD display	0 to +70°C, 0 to +70°C, LCD display
Operating pressure	ModBus
Operating pressure	ModBus RTU, Advantech ADAM
Operating pressure	110 to 115200 Bd
Operating pressure	0.025mm - 0.05mm
IP rating	IP54, IP40
Operating pressure	9-30Vdc, 6mA
Operating pressure	1m, 2m or 4m
Operating pressure	88.5 x 114 x 39.5 mm (W x H x D), 88 mm, 18mm
Operating pressure	290g - 1m
Operating pressure	3