

T7411 - RS485 - kopie - kopie

Model: T7411-4

Temperature sensor cable lengths 1m, 2m, 4m
RS485 interface 1 or 2 or 4 wire LCD display



Features

Humidity	0 to 100%
Humidity accuracy	$\pm 2.5\%$ RH 5 to 95% at 23°C
Temperature	$\pm 0.4^{\circ}\text{C}$ -30 to +100°C $\pm 0.4\%$ RH +100°C
Temperature accuracy	$\pm 1.5^{\circ}\text{C}$ T < 25°C RH > 30% -60 to +80°C
Humidity range	0 to 100%
Temperature range	$\pm 1.5\text{g/m}^3$ T < 25°C 0 to 400 g/m3
Humidity range	$\pm 2\text{g/kg}$ T < 35°C 0 to 550 g/kg
Humidity range	$\pm 2\text{g/kg}$ T < 35°C 0 to 995 g/kg
Humidity range	$\pm 3\text{kJ/kg}$ T < 25°C 0 to 995 kJ/kg
Pressure	600 to 1100hPa
Pressure accuracy	$\pm (1,3\text{hPa} + 0.06\% \text{ of reading})$ at 23°C from 800 to 1100hPa
Pressure range	hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2
Temperature range	-30 to +80°C
LCD display	Monochrome +70°C +70°C LCD
Communication	ModBus RTU Advantech ADAM
Communication	110 to 115200 Bd
Communication	0.025mm - 0.05mm
IP rating	IP54, IP40
Power	9-30Vdc, 0.5W
Cable length	1m, 2m or 4m
Dimensions	88.5 x 114 x 39.5 mm (W x H x D), 88 mm, 18mm
Weight	210g - 1m
Warranty	3