

T7418 - 温湿度湿度传感器RS485

型号: T7418



温湿度湿度传感器

温湿度湿度传感器HVAC系统RS485接口KU68接口

参数

湿度范围	5 to 95%
湿度精度	±2.5%RH 5 to 95% at 23°C
温度范围	±0.5°C
温度精度	±0.5°C
温度范围	±1.6°C (T < 25°C) RH > 30% -60 to +80 °C
湿度精度	±1.5g/m ³ (T < 25°C) 0 to 400 g/m ³
湿度精度	±2g/kg (T < 35°C) 0 to 550 g/kg
湿度精度	±2.2g/kg (T < 35°C) 0 to 995 g/kg
湿度精度	±3kJ/kg (T < 25°C) 0 to 995 kJ/kg
湿度范围	600 to 1100hPa
湿度精度	±(1,3hPa+0.06%RH) at 23°C from 800 to 1100hPa
湿度单位	hPa, kPa, mbar, mmHg, inHg, inH ₂ O, PSI, oz/in ²
湿度接口	ModBus RTU/Advantech ADAM
湿度接口	110 to 115200 Bd
IP等级	IP20
湿度电压	9-30Vdc, 0.5W
湿度尺寸	88 x 106 x 33 mm (W x H x D)
湿度材料	ABS
湿度重量	150g
湿度寿命	3年