

# T7510 -

T7510

t-line



LCD

|     |                                                |
|-----|------------------------------------------------|
|     | 0 to 100%                                      |
|     | ±2.5%5 to 95% at 23°C                          |
|     | ±0.6°C                                         |
|     | 600 to 1100hPa                                 |
|     | ±1.3hPa at 23°C                                |
|     | 0.1°C, 0.1%RH, 0.1hPa                          |
|     | 2s                                             |
|     |                                                |
|     |                                                |
|     | hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2 |
|     | ±1.5°C<25°C RH>30%<br />-60 to +80 °C          |
|     |                                                |
|     | -30 to +80°C                                   |
| IP  | IP30,IP40                                      |
| LAN | RJ-4510Base-T100Base-TX                        |
|     | WWW, ModbusTCP, SNMPv1, SOAP                   |
|     | E-mail (SMTP)SNMP TrapSyslog                   |
|     | T-Sensor, WWW                                  |
|     | 9-30Vdc, 1W                                    |
|     | 5.5 x 2.1mm                                    |
|     | 88.5 x 147.5 x 39.5mm (W x H x D), 75 mm       |
|     | 155g                                           |
|     | 3                                              |